

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 March 2004 (18.03.2004)

PCT

(10) International Publication Number
WO 2004/023840 A2

(51) International Patent Classification⁷:

H04R

(74) Agents: NETTLETON, John, Victor et al.; Abel & Imray, Chartered Patent Attorneys, 20 Red Lion Street, London WC1R 4PQ (GB).

(21) International Application Number:

PCT/GB2003/003771

(22) International Filing Date:

1 September 2003 (01.09.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0220575.5

4 September 2002 (04.09.2002)

GB

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): B & W LOUDSPEAKERS LIMITED [GB/GB]; Dale Road, Worthing BN11 2BH, Sussex (GB).

(72) Inventor; and


(75) Inventor/Applicant (*for US only*): NEVILL, Stuart, Michael [GB/GB]; 252 Bellegrove Road, Welling, Kent DA16 3RT (GB).

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: SUSPENSION FOR THE VOICE COIL OF A LOUDSPEAKER DRIVE UNIT



(57) Abstract: A suspension (30), for the voice coil of a loudspeaker drive unit, comprises an inner ring (32) to be connected to the voice coil of the loudspeaker drive unit; an outer ring (34) to be connected to the chassis of the loudspeaker drive unit; and a plurality of radial spoke-like members (36, 42) connecting the inner ring to the outer ring. The radial spoke-like members (36, 42) are free of compressive stress between their ends. The spoke-like members (42) are of greater lateral stiffness than the spoke-like member's (36) and are substantially X-shaped.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.